



Main

Range of product	Conext SW
Device short name	SW 4024
Product or component type	Inverter/Charger

Complementary

Type of signal	True sine wave (invert mode)
Continuous power	4000 W overload for output (invert mode) , duration: 30 min 7000 W surge for output (invert mode) , duration: 5 s 3400 W for output (invert mode)
Peak output current	41 A for short circuit
Network frequency	50/60 Hz for output (selectable)
Output voltage	12...32 V DC (charge mode) 24 V DC (charge mode) for nominal mode 240 V AC (invert mode) 120 V AC (invert mode)
Output current	90 A (charge mode)
Input voltage	20...34 V DC (invert mode) 135...270 V AC (charge mode) 95...135 V AC (charge mode) 240 V AC (charge mode) 120 V AC (charge mode)
Input current	13 A (charge mode)
Efficiency	92 % (invert mode) 90 % (charge mode)
Cos phi	> 0.98 for input
Power consumption in W	< 8 W for search mode
Battery type	FLA Gel AGM
Relay type	Automatic transfert relay at 30 A
Transfer time	<= 16.7 ms
Provided equipment	Battery temperature sensor included for temperature compensation
Height	418 mm
Width	341 mm
Depth	197 mm
Product weight	28.1 kg

Environment

Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...85 °C
Standards	UL 1741 CSA C22.2 No 107.1
Product certifications	CSA

www.MatrixEnergy.ca
Toll Free: 1-866-630-5630



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.