



Main

Range of product	Xantrex XW
Device short name	XW4548-120/240-60
Product or component type	Hybrid inverter / charger
Network number of phases	Single phase
Type of signal	True sine wave
Continuous power	4500 W AC - 120 V) 4500 W AC - 240 V)

Complementary

Feature available	75 A - phase to neutral (L-N) - 20 s 40 A - phase to phase (L-L) - 20 s
Network frequency	60 Hz +/- 0.1 Hz (output)
Cos phi	0.98
Harmonic distortion	< 5 %
Input voltage	50.4 V DC 120 V AC (L-N) - bypass/charge mode 240 V AC (L-L) - bypass/charge mode
Input voltage limits	44...64 V DC 80...150 V AC (L-N) - bypass/charge mode 160...270 V AC (L-L) - bypass/charge mode 108...130 V +/- 1.5 V AC (L-N) - sell mode 214...260 V +/- 3.0 V AC (L-L) - sell mode
Input current	96 A DC at rated power
Input frequency	59.4...60.4 Hz +/- 0.05 Hz - sell mode 55...65 Hz - bypass/charge mode (default) 44...70 Hz - bypass/charge mode (allowable)
Charging current	85 A
Efficiency	95 % - low-load 93 % CEC weighted 90.2 % - maximum charge rate
Power consumption in W	< 8 W - search mode
Communication network type	Xanbus
Device mounting	Wall mounted
Provided equipment	Battery temperature sensor included for temperature compensation
Height	580 mm
Width	410 mm
Depth	230 mm
Product weight	53.5 kg

Environment

NEMA degree of protection	NEMA Type 1
Ambient air temperature for operation	-25...70 °C
Standards	CSA 107.1 UL 1741
Product certifications	FCC Class B



296 Labrosse Avenue, Pointe-Claire, QC, Canada, H9R 5L8
Tel: (514) 630-5630 Toll Free: 1-866-630-5630 Fax: (514) 426-9123
info@matrixenergy.ca www.matrixenergy.ca